

XS618B2PAL01M12

Inductive Proximity Sensor , 12/24VDC, 100mA,
Osiprox, Tubular, 18mm



List Price \$105.00 USD

Availability **Non-Stock Item:** This item is not normally stocked in our distribution facility.

Technical Characteristics

Ampere Rating	100mA
Approvals	UL Listed - CSA Certified - CE Marked
Body Type	Tubular
Marketing Trade Name	Osiprox
Catalog Reference Number	9006CT0101
Connection Type	M12 Connector with pigtail (0.1m)
Enclosure Material	Nickel Plated Brass
Enclosure Rating	NEMA 3/4X/6P/12/13
Enclosure Type	Water tight, Dust tight, Oil tight, Corrosion Resistant and Submersible (Indoor/Outdoor)
LED Indicator	Output: Yellow - Power/Teach: Green
Maximum Operating Frequency	1000Hz
Maximum Voltage Rating	36VDC
Output	DC 3-Wire (PNP) - 1 N.O.
Nominal Sensing Distance	10mm
Supply Voltage	12/24VDC
Sensor Diameter	18mm
Type	XS6
Operating Temperature Range	-13 to 158 Degrees F (-25 to 70 Degrees C)

Shipping and Ordering

Category	22486 - Sensors, Proximity, XS
Discount Schedule	DS2
Article Number	785901455790
Package Quantity	1
Weight	0.21 lbs.
Availability Code	N
Returnability	N

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.